

350P/360P



Saving more lives for less.™

# FEATURES AND BENEFITS











### SAMARITAN 350P/360P

### COMPACT, EASY-TO-USE, LIFESAVING TECHNOLOGY

The samaritan® PAD family of public access defibrillators is designed especially for use in public areas by providing a sophisticated defibrillator for adult or pediatric use inside a lightweight and easy-to-operate system, and offers all the key features of the samaritan PAD products.

The samaritan PAD 360P is a fully automatic defibrillator designed to analyse heart rhythm and automatically deliver a life-saving electrical shock (if needed). The SAM 350P is a semi-automatic variant, which will advise the rescuer exactly when they need to press the shock button. This allows a faster shock and puts the rescuer more in control of the situation.

### **EASY-TO-FOLLOW GUIDES**


**User-friendly.** The samaritan PAD features easy-to-understand visual and voice prompts that guide a user through the process including CPR coaching.

**Always ready.** A System Status Ready Indicator flashes to show that the complete system is operational and ready for use. The device automatically runs a self-check each week.

**360P automatic shock.** The samaritan PAD 360P only has one button – ON/OFF, ensuring straightforward operation for all levels of rescuer. After analysing heart rhythm, the samaritan PAD 360P will, if needed, automatically deliver a shock eliminating the need for the rescuer to push a shock button.



### **COMPACT IN SIZE, BIG ON ABILITY**



**Highest level of dust/moisture protection.** The samaritan PAD has a rating of IP56, providing the highest level of protection from dust or water ingress in the industry.

**Durable.** The samaritan PAD 500P resists shock and vibration and comes with a shock-proof carry case free of charge

**Advanced technology.** The samaritan PAD 500P utilizes proprietary electrode technology, advanced and stable firmware, and patented SCOPE™\* Biphasic Technology to assess rhythm and recommend a shock if defibrillation is necessary.

\*See overleaf for more information



#### **PAD PAK TECHNOLOGY**

### Low cost of ownership.

Pad Pak cartridge has a shelf life of four years from date of manufacture, offering significant savings over competitive defibrillator brands that require separate battery and pad units.




### Combined expiration date.

Cartridge combines battery and electrode pads, with one expiration date to monitor.

#### Great for children.

The HeartSine PAD's built-in intelligence and unique pediatric Pad-Pak ensure the appropriate energy level is delivered for children.

# TECHNICAL SPECIFICATIONS



PHYSICAL	WITH PAD-PAK™ INSERTED
Size:	20 cm x 18.4 cm x 4.8 cm
Weight:	1.1kg including Pad-Pak battery

Size:	$20 \text{ cm} \times 18.4 \text{ cm} \times 4.8 \text{ cm}$	
Weight:	1.1kg including Pad-Pak battery	

### **DEFIBRILLATOR**

Self-Compensating Output Pulse Envelope (SCOPE) Biphasic waveform. Optimized biphasic Waveform: escalating waveform compensates energy, slope and envelope for patient impedance

### PATIENT ANALYSIS SYSTEM

Method:	Evaluates patient's ECG, signal quality, electrode contact integrity and patient impedance to determine if defibrillation is required
Sensitivity/Specifity:	Meets ISO 60601-2-4

### **ENVIRONMENTAL**

Operating/Standby Temperature:	0°C to 50°C
Temporary Transportation Temerature:	-10°C to 50°C for up to two days. Unit must be returned to standby/operating temperature for 24 hours before use.
Relative Humidity:	5% to 95% (non-condensing)
Water Resistance:	IEC 60529/EN 60529 IP56
Altitude	0 – 4,575 meters
Shock	MIL STD 810F Method 516.5, Procedure I (40 Gs)
Vibration:	MIL STD 810F Method 514.5+, Category 4 Truck Transportation – US Highways, Category 7 Aircraft – Jet 737 & General Aviation (Exposure
EMC:	EN 60601-1-2
Radiated emissions:	EN55011
Electrostatic Discharge RF Immunity:	EN61000-4-3 80MHZ-2.5GHZ (10 V/m)
Magnetic Field Immnity:	EN61000-4-8 (3 A/m)
Aircraft:	RTCA/DO-160F, Section 21 (Category M)
Drop Tested:	1 metre

### **ENERGY SELECTION**

Adult:	Shock 1: 150J;	Shock 2: 150J;	Shock 3: 200J
Paediatric:	Shock 1: 50J;	Shock 2: 50J;	Shock 3: 50J

### **CHARGING TIME**

New Battery:	Typically 150J in < 8 seconds, 200J in < 12 seconds
After 6 Discharges:	Typically 150J in < 8 seconds, 200J in < 12 seconds

### **EVENT DOCUMENTATION**

Туре:	Internal Memory
Memory Capacity	90 minutes of ECG (full disclosure) and event/incident recording
Playback capabilities:	Custom USB cable directly connected to PC and Saver™ EVO Windows-based data review software

### **MATERIALS USED**

Housing	ABS, Santoprene
Electrodes	Hydrogel, Silver, Aluminium and Polyester

### PAD PAK - ELECTRODE & BATTERY CARTRIDGE

Shelf Life:	4 years from manufacture date
Weight:	0.2kg
Size:	10 cm x 13.3 cm x 2.4 cm
Battery Type:	Lithium Manganese Dioxide (LiMnO2)
Capacity:	> 60 shocks at 200J 18V, 1.5 Amp Hrs
Electrodes:	HeartSine samaritan® disposable defibrillation pads are supplied as standard with each device
Placement:	Anterior-lateral (Adult); Anterior-posterior (Paediatric)
Active Gel Area:	100 cm2
Cable Length:	1 metre



The HeartSine samaritan has lower running costs than ANY other AED across its 8 year warranty period



