

INTRODUCING THE PELICAN™ 3410/M



CONFIGURATIONS

STANDARD VERSION	Magnet	3410M
	No Magnet	3410
SAFETY CERTIFIED	Magnet	3415M
	No Magnet	3415

PERFORMANCE DATA

	3410M / 3410	3415M / 3415
LIGHT OUTPUT	Up to 653 Lumens	Up to 329 Lumens
RUN TIME	Up to 61 Hours	Up to 15 Hours
LIGHT LEVELS	High, Medium, Low	High
MODES	Spot / Flood / Spot & Flood	
BATTERIES	3 AA	
IP RATING	IPX8 (1m)	
CERTIFICATIONS	N/A	CI II III, D1
COLORS	■ Photoluminescent	■ High Visibility Yellow

Performance data is to FL 1 Standards. Visit Pelican.com for full specifications.

SAFETY CERTIFIED MODEL

PELICAN™ 3415/M

CLASS I II III, DIVISION 1

Certified to provide the security needed for most hazardous locations



653 LUMENS / 61H RUN TIME

Stop working in the dark. With a brightness of up to **653 lumens**, these flashlights are so intense that you'll see all the details in the darkest job sites. And with up to **61 hours of run time** you'll have enough light for several shifts on just one set of batteries. It's all the brightness and run time you'll need to finish the job.



3410/M BROCHURE
3410/M FLASHLIGHT



DESIGNED IN
USA

SINCE 1976

LIGHT BE NIMBLE

THE MOST VERSATILE PRO-GRADE
FLASHLIGHT IN THE WORLD.




For warranty details go to www.pelican.com/warranty
©2017 Pelican Products, Inc. All trademarks are registered and/or unregistered trademarks of Pelican Products, Inc., its subsidiaries and/or affiliates.
Part No. 0030-TFB-000 SE/17



90° ARTICULATING HEAD

The attached clip allows for hands-free operation. Plus the **90° Articulating** head allows you to get light where you need it, when you need it.



MAGNETIC CLIP

The integrated **Magnetic Clip*** allows for additional hands-free applications. Illuminating compact air ducts or car engines just got easy.

* 3410M / 3415M models



FLOOD / SPOT BEAM

See farsighted, nearsighted or both with just the push of a button. **Flood Mode** lets you see the whole work area, **Spot Mode** illuminates long distances, or select **Spot and Flood Mode** to see both near and far.

